Version: 01.09.2023

GUIDELINES ON THE CLASSIFICATION AND SURVEY OF YACHTS

ND No. 2-030101-041-E



St. Petersburg 2021

GUIDELINES ON THE CLASSIFICATION AND SURVEY OF YACHTS

Guidelines on the Classification and Survey of Yachts of Russian Maritime Register of Shipping have been approved in accordance with the established approval procedure and come into force on 1 January 2021.

The present edition is based on CL No. 340-48-752c of 22.07.2014 taking into account the amendments developed immediately before publication.

The Guidelines are published in electronic format in Russian and English.

The Guidelines are intended for surveyors, crews of the ships and shipowners.

REVISION HISTORY¹

(purely editorial amendments are not included in the Revision History)

(purely editorial amendments are not included in the Revision History)					
Amended	Information on amendments	Number and	Entry-into-force		
paras/chapters/		date of the	date		
sections		Circular Letter			
Para 1.1.4	Scope of application of the Guidelines	340-04-1790c	15.07.2022		
	has been specified (reference to	of 07.07.2022			
	the number of passengers has been				
	deleted)				
Para 1.1.5	Characteristics of yachts to which	340-04-1801c	15.09.2022		
<u>1 ala 1.1.5</u>	these Guidelines do not apply have	of 09.08.2022	13.03.2022		
		01 09.06.2022			
D 404	been specified	0.40.04.4700	45.07.0000		
Para 1.2.1	Para has been completely revised in	340-04-1790c	15.07.2022		
	connection with deletion of the	of 07.07.2022			
	definitions used in other RS rules				
Para 2.1.3	Requirements for length and gross	340-04-1790c	15.07.2022		
	tonnage of yachts have been	of 07.07.2022			
	specified				
Para 2.1.4	Requirements for length and gross	340-04-1790c	15.07.2022		
	tonnage of yachts have been	of 07.07.2022			
	specified				
Para 2.2	Requirements for classification of	340-04-1790c	15.07.2022		
T did Z.Z	yachts with descriptive notation	of 07.07.2022	10.07.2022		
	Pleasure yacht and with $L \le 24$ m as	01 07.07.2022			
	well as with descriptive notation				
	· •				
Dava 0.0	Yacht (charter) have been specified	240.04.4700-	45.07.0000		
Para 2.3	Requirements for classification of	340-04-1790c	15.07.2022		
	yachts not stated in 2.2 have been	of 07.07.2022			
	specified				
Para 2.5	Para has been supplemented with	340-04-1743c	12.04.2022		
	descriptive notations Yacht for	of 12.04.2022			
	commercial service, Yacht				
	(charter) — for commercial use and				
	Passenger yacht — for yachts,				
	carrying from 13 to 36 passengers.				
	Reference to the RS rules has been	340-04-1790c	15.07.2022		
	specified	of 07.07.2022			
Para 2.7	Para has been renamed	340-04-1790c	15.07.2022		
- 313 211		of 07.07.2022			
Para 2.7.1.1	Abbreviation "the TSSS Guidelines"	340-04-1790c	15.07.2022		
<u>1 414 2.7.1.1</u>	has been introduced for the	of 07.07.2022	10.07.2022		
	Guidelines on Technical Supervision	01 01.01.2022			
	of Ships in Service				
Doro 2.7.4.7		240 04 4700-	15.07.0000		
Para 2.7.1.7	Requirements for tonnage calculation	340-04-1790c	15.07.2022		
	have been specified	of 07.07.2022	10.04.5555		
Para 2.7.2.1	Para has been supplemented with	340-04-1743c	12.04.2022		
	reference to REG Yacht Code (Red	of 12.04.2022			
	Ensign Group Code), Part A and				
	Part B				

¹ Amendments and additions introduced at re-publication or by new versions based on circular letters or editorial amendments.

Amended	Information on amendments	Number and	Entry-into-force
paras/chapters/		date of the	date
sections		Circular Letter	
Para 2.7.2.4	Requirements for length of the yacht	340-04-1790c	15.07.2022
	have been specified	of 07.07.2022	
Para 2.7.2.8	Requirements for length of the yacht	340-04-1790c	15.07.2022
	have been specified	of 07.07.2022	
Para 2.7.3.3	Requirements for length of the yacht	340-04-1790c	15.07.2022
	have been specified	of 07.07.2022	
Para 2.7.3.4	Requirements for length of the yacht	340-04-1790c	15.07.2022
	have been specified	of 07.07.2022	
Para 2.7.4	Requirements for classification and	340-04-1790c	15.07.2022
	survey of yachts with descriptive	of 07.07.2022	
	notations Yacht for commercial		
	service and Passenger yacht have		
	been specified	0.40.04.4=00	45.05.000
Para 2.8	Para has been renamed	340-04-1790c	15.07.2022
Damas 0.0.4 0.0.4	Descriptores at a house because a cifical	of 07.07.2022	45.07.0000
Paras 2.8.1 — 2.8.4	Requirements have been specified	340-04-1790c	15.07.2022
	considering length of the yacht and intended use	of 07.07.2022	
Para 2.8.5	Requirements for performing	311-05-1970c	01.09.2023
<u>Fala 2.0.5</u>	the Tonnage calculation for yachts	of 11.08.2023	01.09.2023
	classed without assignment of	01 11.00.2023	
	the RS class have been specified		
Para 3.6.3.2	Reference to the applicable	340-04-1790c	15.07.2022
1 414 0101012	requirements has been specified	of 07.07.2022	1010112022
Para 3.6.3.8	Reference to the applicable	340-04-1790c	15.07.2022
	requirements has been specified	of 07.07.2022	
Para 3.6.4.5	Reference to the applicable	340-04-1790c	15.07.2022
	requirements has been specified	of 07.07.2022	
Para 3.6.4.11	Reference to the applicable	340-04-1790c	15.07.2022
	requirements has been specified	of 07.07.2022	
Para 3.6.5.5	Reference to the applicable	340-04-1790c	15.07.2022
	requirements has been specified	of 07.07.2022	
Para 3.6.5.10	Reference to the applicable	340-04-1790c	15.07.2022
	requirements has been specified	of 07.07.2022	45.05.000
Para 3.7	Para has been completely revised.	340-04-1790c	15.07.2022
	Requirements for types and terms of	of 07.07.2022	
	periodical surveys have been		
	amended depending on descriptive notation and length of the yacht		
Para 3.8	New para 3.8 has been introduced	340-04-1790c	15.07.2022
<u>ı aıa 3.0</u>	containing requirements for the scope	of 07.07.2022	13.01.2022
	of annual survey	01.01.2022	
Para 3.9	New para 3.9 has been introduced	340-04-1790c	15.07.2022
<u> </u>	containing requirements for the scope	of 07.07.2022	. 5.5
	of intermediate survey		
Para 3.10	New para 3.10 has been introduced	340-04-1790c	15.07.2022
	containing requirements for the scope	of 07.07.2022	
	of special survey		
Para 3.11	New para 3.11 has been introduced	340-04-1790c	15.07.2022
	containing requirements for the scope	of 07.07.2022	
	of yacht's bottom survey		

Guidelines on the Classification and Survey of Yachts

Amended	Information on amendments	Number and	Entry-into-force
paras/chapters/		date of the	date
sections		Circular Letter	
Para 3.12	New para 3.12 has been introduced	340-04-1790c	15.07.2022
	containing requirements for the scope	of 07.07.2022	
	of survey of shafting, propellers and AMSS		
Para 3.8	Existing para 3.8 has been	340-04-1790c	15.07.2022
(renumbered	renumbered 3.13	of 07.07.2022	
para 3.13)			
Para 4.2	Para has been completely revised	340-04-1790c	15.07.2022
	considering the amendments to survey schedule	of 07.07.2022	
Para 4.3	Para has been completely revised	340-04-1790c	15.07.2022
	considering the amendments to	of 07.07.2022	
	survey schedule and list of issued		
	documents		
Para 4.6.1	Terminology regarding yachts	340-04-1790c	15.07.2022
	intended for commercial use has been unified	of 07.07.2022	
Para 4.9	Para has been completely revised	340-04-1790c	15.07.2022
	considering the amendments to	of 07.07.2022	
	survey schedule and list of issued		
	documents		

1 GENERAL

1.1 APPLICATION

- **1.1.1** The Guidelines on the Classification and Survey of Yachts¹ have been developed for the purpose of consistent approach and interaction between the Head Office² and Branch Offices of the Russian Maritime Register of Shipping³ in considering the issue of the classification and survey of yachts in service.
- **1.1.2** For the purpose of these Guidelines, classification of yacht means a set of measures and actions on assigning the RS class, except for the case specified in 1.1.3.
- 1.1.3 Classification of yachts flying the RF flag, at the shipowner's discretion, may be carried out without assignment of the RS class and issuance of a classification certificate. This provision applies to yachts used for non-commercial purposes, with the overall length of the hull above 20 m and carrying a maximum of 12 passengers with no more than 18 people on board.

This classification is aimed at assessment of the yacht actual compliance with the applicable RS rules and establishing a category that takes into account probable wind and wave conditions of navigation and a distance to the place of refuge or the shore.

Application of this provision to the yachts flying the flags other than the RF flag is determined by RHO in each particular case.

1.1.4 If not otherwise stated herein, the Guidelines apply to:

the classification of yachts regardless their length;

the classification of yachts regardless of their intended use (commercial or non-commercial).

1.1.5 The Guidelines do not apply for the classification of:

ships weighing up to 200 kg inclusive and with engine power (in case of installation) up to 8 kW inclusive;

undecked non-self-propelled ships the length of which does not exceed 12 m;

sailing racing yachts;

manned submersibles and ship's diving systems;

boats or other floating craft being part of the ship; small craft.

Hereinafter referred to as the "Guidelines".

² Hereinafter referred to as the "RHO".

Hereinafter referred to as the "Register, RS".

1.2 DEFINITIONS AND EXPLANATIONS

1.2.1 Definitions and explanations except for the length *L*, used in these Guidelines are given in the relevant parts of the Rules for the Classification and Construction of Pleasure Craft¹, Rules for the Classification and Construction of Sea-Going Ships, Rules for the Equipment of Sea-Going Ships, Load Line Rules for Sea-Going Ships, Rules for the Classification and Construction of High-Speed Craft as well as in safety standards applied by the Register (refer to 2.7.2.1 of these Guidelines).

For the purpose of these Guidelines the length L is defined as follows:

for yachts intended for non-commercial use for recreation in water bodies, not carrying cargoes and more than 12 passengers, the length L is defined in compliance with the PC Rules as the length of the hull L_H ;

for all other yachts the length L is defined in compliance with the definition specified in Part II "Hull" of the Rules for the Classification and Construction of Sea-Going Ships as the length L_{LL} .

¹ Hereinafter referred to as the "PC Rules".

2 PRINCIPLES OF YACHT CLASSIFICATION

- 2.1 RS Branch Offices competence in considering the issue of yacht classification.
- **2.1.1** Consideration of the issue of classification of yachts having a class (not RS) of another Classification Society subject to verification of compliance with Quality System Certification Scheme of International Association of Classification Societies (IACS)¹, and a gross tonnage above 100, is within the RHO competence.
- **2.1.2** Consideration of the issue of classification of yachts having a class of ACS QSCS, with 100 gross tonnage and below, unless stated otherwise, is within the competence of the RS Branch Office for in-service supervision (planned). Where the yacht classification is carried out outside the area of activity of the RS Branch Office for in-service supervision, the issue of classification is considered by the RS Branch Office responsible for the region where the yacht is located (refer to 2.1.6).
- **2.1.3** Consideration of the issue of classification of yachts, having no ACS QSCS class, with L > 24 m and gross tonnage above 100, is within the RHO competence.
- **2.1.4** Consideration of the issue of classification of yachts having no ACS QSCS class, with $L \le 24$ m and gross tonnage 100 and below, unless stated otherwise, is within the competence of the RS Branch Office for in-service supervision (planned). Where the yacht classification is carried out outside of the area of activities of the RS Branch Office for in-service supervision, the issue of classification is considered by the RS Branch Office responsible for the region where the yacht is located.
- **2.1.5** Consideration of the issue of classification of yachts without assignment of class (refer to 1.1.3) is within the competence of the RS Branch Office for in-service supervision (estimated). Where the yacht classification is carried out outside the area of activity of the RS Branch Office for in-service supervision, the issue of classification is considered by the RS Branch Office responsible for the region where the yacht is located (refer also to 2.1.6)
- **2.1.6** In all cases of transfer of the yacht from class of ACS recognized by the European Union², including the cases specified in <u>2.1.2</u> and <u>2.1.5</u>, under the provisions of 10.6 of Regulation (EU) No 391/2009 of 23.04.2009, the RS Branch Office responsible for consideration of the issue of yacht classification, shall establish the interaction with RHO for timely receipt of relevant information on the List of Surveys Status of the yacht from the losing society. RHO is responsible for exchange of the required information. List of ACS recognized by EU is submitted by RHO upon individual requests.
- **2.2** Classification of yachts with descriptive notation **Pleasure yacht** in the class notation (refer to 2.5 of these Guidelines), with $L \le 24$ m, and yachts with descriptive notation **Yacht (charter)** (refer to 2.5 of these Guidelines) is carried out for compliance with the PC Rules.
 - 2.3 Classification of yachts not specified in 2.2.
- **2.3.1** Classification of yachts of L > 24 m with descriptive notation **Pleasure yacht** in the class notation (refer to 2.5 of these Guidelines) is carried out in compliance with 1.9 of the PC Rules and other safety standards applied by the Register (refer to 2.7.2.1 of these Guidelines), as reasonably practicable. Such practicability is determined by RHO.
- **2.3.2** Classification of yachts of $L \ge 24$ m intended for commercial use is carried out in compliance with the provisions of Part XX "Additional Requirements for Yachts" of the Rules for the Classification and Construction of Sea-Going Ships and other safety standards applied by the Register (refer to 2.7.2.1 of these Guidelines).
- 2.3.3 Yachts with descriptive notation Passenger yacht in the class notation shall comply with the requirements of the Rules for the Classification and Construction of Sea-Going Ships, Rules for the Equipment of Sea-Going Ships applicable to the passenger ships as well as of the Load Line Rules for Sea-Going Ships (for yachts intended for commercial use), Rules for the Prevention of Pollution from Ships Intended for Operation in Sea Areas and Inland Waterways of the Russian Federation (for yachts flying the RF flag) and, if applicable, international

¹ Hereinafter referred to as the "ACS QSCS".

² Hereinafter referred to as the "EU".

conventions, codes and additional requirements of the flag State Maritime Administration¹. The national flag State MA requirements shall take precedence over similar requirements of the RS rules. Yachts carrying more than 36 passengers shall fully comply with all the requirements of the RS rules specified above that apply to passenger ships. List of safety standards applied by the Register is as follows: Red Ensign Group — Yacht Code Part B — Passenger Yacht Code (PYC), Malta Commercial Yacht Code, Marshall Islands Yacht Code. In the absence of national MA standards, it is recommended to use PYC. In case of classification of yachts specified herein and contracted for construction before 14 April 2022, the national flag State MA requirements shall apply. With regard to the flag of the Russian Federation, the Red Ensign Group — Yacht Code Part B shall apply, unless otherwise stated in the RS rules.

- **2.3.4** For classification of yachts without assignment of class (refer to 1.1.3 of these Guidelines), the feasibility and practicability of applying the requirements of other RS rules and safety standards is within the competence of the RS Branch Office responsible for the region where the yacht is located in cooperation with the RS Branch Office for in-service supervision and, if necessary, with RHO.
- **2.4** Process of yacht classification includes also verification of equipment, outfit, facilities for environment pollution prevention and the load line marks for compliance with the PC Rules, unless compliance with other standards is prescribed by the flag State MA (except for RF MA). Where the flag State national standards are available, the yacht shall comply with them within the prescribed scope instead of the relevant requirements of the PC Rules, except for the class-related issues.
- **2.5** For assignment of class to yachts, the principles of yacht classification as well as class notations and distinguishing marks specified in Section 2 of Part I "Classification" of the Rules for the Classification and Construction of Sea-Going Ships are used with adding to the class notations, if necessary, the distinguishing marks or descriptive notations stipulated by other RS rules (e.g., the Rules for the Classification and Construction of High-Speed Craft or the PC Rules).

Descriptive notation in the class notation is indicated as follows:

Pleasure yacht — for yachts intended for non-commercial use for recreation in water bodies, not carrying cargoes and more than 12 passengers;

Yacht (charter) — for yachts of less than 24 m in length, intended for commercial use, not carrying cargoes and more than 12 passengers;

Yacht for commercial service — for yachts of 24 m in length and above, intended for commercial use, not carrying cargoes and more than 12 passengers;

Passenger yacht — for yachts intended for commercial and non-commercial use, carrying from 13 to 36 passengers and not carrying cargoes.

- **2.6** The purpose of the yacht use (commercial or non-commercial) as well as the necessity of assignment of the RS class to the yachts flying the RF flag and falling under the definition of pleasure craft in accordance with Article 7 (Item 4) of the Merchant Shipping Code of the Russian Federation², and which may be classed without assignment of the RS class (refer to 1.1.3), is determined by the shipowner and reported to the Register in case of application for classification.
 - 2.7 Procedure for yacht classification.

Summarized list of requirements applicability to the yacht classification is given in Table 2.7.

- 2.7.1 Classification of yachts classed by ACS QSCS.
- **2.7.1.1** The procedure for transfer of class specified in 5.1 and 5.2 of Part II "Carrying Out Classification Surveys of Ships" of the Guidelines on Technical Supervision of Ships in Service³ shall apply taking into account the following.
- **2.7.1.2** No assessment of the yacht compliance with the PC Rules and other RS rules is required.

Hereinafter referred to as the "RF MSC".

Hereinafter referred to as the "MA".

³ Hereinafter referred to as the "TSSS Guidelines".

2.7.1.3 For the yachts of gross tonnage above 100, it is required to submit plans and documentation in the scope prescribed by 5.2.3.10 of Part II "Carrying Out Classification Surveys of Ships" of the TSSS Guidelines, as applicable.

For the yachts of 100 gross tonnage and below, it is required to submit plans and documentation in the scope necessary for:

the yacht identification (plans or diagrams showing general arrangement of the yacht including location of machinery, arrangements, equipment and outfit as well as systems);

verification of stability, tonnage and freeboard of the yacht (if necessary).

- **2.7.1.4** No verification of strength characteristics of the yacht's hull for compliance with the RS rules is required.
- **2.7.1.5** The calculation of permissible residual scantlings of hull members in compliance with the RS rules is not required in case the yacht has no ice class.
- **2.7.1.6** The onboard documentation on stability is temporarily approved by the RS surveyor for a period not more than 12 months if any deficiencies not affecting the safe operation of the yacht are found, in other cases it is approved for a full term. In case of revealing of the above-mentioned deficiencies, the requirement on their rectification is imposed. If the documentation is temporarily approved, the final review and approval of documentation is performed by RHO.
- **2.7.1.7** Tonnage Calculation is required, except for the yachts having the International Tonnage Certificate issued by ACS QSCS or the flag State MA.
- **2.7.1.8** Freeboard calculation is required for the yachts used for commercial purposes, except for the yachts having the International Load Line Certificate or any other Load Line Certificate issued by ACS QSCS or the flag State MA and complying with the safety standards.
- 2.7.2 Classification of yachts not classed by ACS QSCS but complying with safety standards applied by the Register.
 - **2.7.2.1** The Register applies the following safety standards:

Directive 2013/53/EU:

IMMARBE's Codes of Standards for Yachts, in commercial or private use (The Small Yacht Code, The Large Yacht Code, The Super Yacht Code);

Commercial yacht code (Merchant Shipping Directorate, within the Authority for Transport in Malta);

LY3 Code (The Large Commercial Yacht Code), developed by United Kingdom Maritime and Coastguard Agency (UK MCA);

REG Yacht Code (Red Ensign Group Code), Part A and Part B;

other rules and codes upon agreement with RHO.

- **2.7.2.2** The procedure for assignment of class specified in 5.1 and 5.3 of Part II "Carrying Out Classification Surveys of Ships" of the TSSS Guidelines shall apply taking into account the following.
- **2.7.2.3** No assessment of the yacht compliance with the PC Rules and other RS rules is required.
- **2.7.2.4** For commercial yachts with $L \ge 24$ m and non-commercial yachts with L > 24 m or gross tonnage above 100 (by the higher criterion value), it is required to submit plans and documentation in the scope prescribed by 5.3.4 of Part II "Carrying Out Classification Surveys of Ships" of the TSSS Guidelines, as applicable.

For other yachts, it is required to submit plans or diagrams necessary for the yacht identification (plans or diagrams showing general arrangement of the yacht including location of machinery, arrangements, equipment and systems).

- **2.7.2.5** No verification of strength characteristics of the yacht's hull for compliance with the RS rules is required.
- **2.7.2.6** The calculation of permissible residual scantlings of hull members in compliance with the RS rules is not required in case the yacht has no ice class.

- **2.7.2.7** The onboard documentation on stability is temporarily approved by the RS surveyor for a period not more than 12 months if any deficiencies not affecting the safe operation of the yacht are found, in other cases it is approved for a full term. In case of revealing of the above-mentioned deficiencies, the requirement on their rectification is imposed. If the documentation is temporarily approved, the final review and approval of documentation is performed by RHO.
- **2.7.2.8** Tonnage calculation is required, except for the yachts having the International Tonnage Certificate issued by ACS QSCS or the flag State MA.
- **2.7.2.9** Freeboard calculation is required for the yachts used for commercial purposes, except for the yachts having the International Load Line Certificate or another Load Line Certificate issued by ACS QSCS or the flag State MA and complying with the safety standards.
- 2.7.3 Classification of yachts not classed by ACS QSCS and not complying with safety standards applied by the Register.
- **2.7.3.1** The procedure for class assignment specified in 5.1 and 5.3 of Part II "Carrying Out Classification Surveys of Ships" of the TSSS Guidelines shall apply taking into account the following.
- **2.7.3.2** Assessment of the yacht compliance with the PC Rules and other RS rules is required at the first stage of the procedure.
- **2.7.3.3** For commercial yachts with $L \ge 24$ m and non-commercial yachts with L > 24 m, it is required to submit plans and documentation in the scope prescribed by 5.3.4 of Part II "Carrying Out Classification Surveys of Ships" of the TSSS Guidelines, as applicable.

For commercial yachts with L < 24 m and non-commercial yachts with $L \le 24$ m, it is required to submit plans and documentation in the scope necessary for:

the yacht identification (plans or diagrams showing general arrangement of the yacht including location of machinery, arrangements, equipment and systems);

qualitative assessment of the yacht compliance with the PC Rules and other RS rules;

verification of strength characteristics of hull, stability, tonnage and freeboard of the yacht for compliance with the RS rules.

- **2.7.3.4** For commercial yachts with $L \ge 24$ m and non-commercial yachts with L > 24 m, the verification of strength characteristics of the hull for compliance with the RS rules is required including calculation of permissible residual scantlings of hull members made of steel and aluminium alloys in compliance with the RS rules.
- **2.7.3.5** Development of the new or appraisal of the existing documentation on stability is required in compliance with the requirements of the PC Rules taking into account the results of inclining test.
 - **2.7.3.6** Tonnage calculation is required.
 - **2.7.3.7** Freeboard calculation for the yachts used for commercial purposes is required.
- **2.7.3.8** If the yacht had the ACS QSCS class from time of construction, but lost it later, the yacht classification is carried out taking into account the following:

assessment of the yacht compliance with the PC Rules and other RS rules shall be carried out to the extent sufficient for confirmation that no alterations are made to the yacht during its being without the ACS QSCS class;

all alterations not approved by ACS QSCS shall be eliminated or technically substantiated with submission of certificates, conducting analysis, tests, etc.

In lieu of $\underline{2.7.3.4} - \underline{2.7.3.7}$, the provisions of $\underline{2.7.1.4} - \underline{2.7.1.8}$ shall apply taking into account that instead of losing ACS QSCS, the ACS QSCS, to which class the yacht was constructed or under which class the yacht was operated, shall be understood.

2.7.3.9 If the yacht has a class of ACS recognized by EU, except for ACS QSCS, the classification is carried out taking into account the exchange of information with ACS QSCS under the provisions of 10.6 of Regulation (EU) No 391/2009 (refer also to <u>2.1.6</u>). RHO is responsible for exchange of the required information. List of ACS recognized by EU is submitted by RHO upon individual requests.

2.7.4 Classification and survey of yachts with $L \ge 24$ m, intended for commercial use, carrying up to 12 passengers and not carrying cargoes (**Yacht for commercial service**), as well as yachts intended for commercial or non-commercial use, carrying from 13 to 36 passengers and not carrying cargoes (**Passenger yacht**), and yachts carrying more than 36 passengers (**Passenger ship**) are performed in compliance with the Rules for the Classification Surveys of Ships in Service¹.

Table 2.7 Summarized list of requirements applicability to the yacht classification

Summarized list of requirements applicability to the yacht classification Requirements Procedure for yacht classification Nos. Having no class of ACS QSCS Classed by ACS Having no class of **QSCS** ACS QSCS but and not complying with the complying with the applicable safety standards applicable safety Not constructed Constructed to standards to the class of the class of ACS QSCS ACS QSCS Applicable procedure 2.7.2.2 2.7.1.1 Assessment of the Not required (refer Not required (refer Required (refer Required to vacht compliance with to 2.7.1.2) to 2.7.2.3) to 2.7.3.2) confirm the the PC Rules and absence of other RS rules (refer alterations (refer to 3.4) to 2.7.3.8) Required (refer to 2.7.3.3) Submission of plans Required (refer Required (refer and technical to 2.7.1.3) to 2.7.2.4) documentation (refer to 3.5.3) Verification of Not required (refer Not required (refer Required (refer Not required strength to 2.7.1.4) to 2.7.2.5) to 2.7.3.4) (refer to 2.7.3.8 characteristics of the and 2.7.1.4) yacht's hull for compliance with the RS rules (refer to 3.5.2) Calculation of 2.7.1.5 2.7.2.6 Required (refer 2.7.3.8 permissible residual and <u>2.7.1.5</u> to 2.7.3.4) scantlings of steel hull members (refer to 3.5.2) Assessment of 2.7.1.6 2.7.2.7 Required upon Within 12 months stability for the inclining test after completion compliance with results prior to of classification the RS rules (refer completion of (refer to 2.7.3.8 to <u>3.5.</u>4) classification and 2.7.1.6) (refer to 2.7.3.5) Tonnage calculation Required if no Required if no Required if no Required (refer (refer to 3.5.5) Measurement Measurement to 2.7.3.6) Measurement Certificate issued by Certificate issued by Certificate issued ACS QSCS or the ACS QSCS or the by ACS QSCS or flag State MA is flag State MA is the flag State MA available (refer available (refer is available (refer to <u>2.7.1.7</u>) to 2.7.2.8) to 2.7.3.8 and

2.7.1.7)

Hereinafter referred to as the "CSSS Rules".

	Requirements	Procedure for yacht classification			
Nos.		Classed by ACS	Having no class of	Having no clas	s of ACS QSCS
		QSCS	ACS QSCS but		plying with the
			complying with the	applicable sa	fety standards
			applicable safety	Not constructed	Constructed to
			standards	to the class of	the class of
				ACS QSCS	ACS QSCS
8	Freeboard	Required if no Load	Required if no Load	Required (refer	
	calculation for the	Line Certificate issued		to <u>2.7.3.7</u>)	Load Line
	yachts used for	by ACS QSCS or the	issued by ACS		Certificate issued
	commercial purposes		QSCS or the flag		by ACS QSCS or
	(refer to <u>3.5.6</u>)	available (refer	State MA is		the flag State MA
		to <u>2.7.1.8</u>)	available (refer		is available (refer
			to <u>2.7.2.9</u>)		to <u>2.7.3.8</u>
					and <u>2.7.1.8</u>)
9	Scope of initial	Taking into account	Complete special		cial survey (refer
	survey (refer to 3.6)	the List of Surveys	survey (refer	to 3	<u>3.6.5</u>)
		Status issued by ACS			
		QSCS (refer to <u>3.6.3</u>)			

2.8 Details of classification of yachts flying the RF flag.

- **2.8.1** In addition to principles specified in $\underline{2.7}$, for the classification of yachts flying the RF flag, the provisions of $\underline{2.8.2} \underline{2.8.4}$ shall be taken into account.
- **2.8.2** Yachts of length $L > 20 \,\mathrm{m}$ used for non-commercial purposes fall under the definition of pleasure craft¹ in accordance with Article 7 (Item 4) of the RF MSC and, at the shipowner's discretion, may be classed without assignment of the RS class (refer to $\underline{1.1.3}$ of these Guidelines).
- **2.8.3** Yachts with the length of the hull (overall) above 20 m, as defined in the Rules for the Classification and Survey of Small Craft, intended for commercial use shall be classed in accordance <u>2.7</u> of these Guidelines with assignment of the RS class and issuance of the Classification Certificate.
- **2.8.4** Yachts with the length of the hull (overall) of 20 m and below, as defined in the Rules for the Classification and Survey of Small Craft, with the total number of persons on board not more than 12 people intended for commercial use fall within the definition² of small craft in accordance with Article 7 (Item 3) of the RS MSC and are classed in compliance with the Rules for the Classification and Survey of Small Craft.
- **2.8.5** For the yachts classed without assignment of the RS class, the procedure for classification of yachts, specified in $\underline{2.7.1}$, $\underline{2.7.2}$ or $\underline{2.7.3}$, as applicable, shall be applied, while no Tonnage calculation is required.
- **2.8.6** For the yachts classed without assignment of the RS class but transferred from ACS QSCS class or class of ACS recognized by EU, the provisions of $\underline{2.1.6}$ and $\underline{2.7.3.9}$ shall be met.

¹ According to the RF MSC, pleasure craft means a ship, the total number of persons on board of which shall not exceed 18 people, including a maximum of 12 passengers, and which is used for non-commercial purposes and intended for recreation in water bodies

According to the RF MSC, small craft means a ship the length of which shall not exceed 20 m and the total number of persons on board of which shall not exceed 12 people.

3 PREPARATION FOR SURVEYS

3.1 The RS Branch Office which, according to <u>2.1</u>, considers the issue of classification shall notify the shipowner in written form of the classification procedure specified in <u>2.7</u> taking into account <u>2.8</u>, and upon receipt of the written consent of the shipowner in accordance with the established procedure arranges the performance of the initial survey of the yacht.

In cases where consideration of the issue of the yacht classification is within the RHO competence, the initial survey may be commenced only upon receipt of the RHO authorization.

3.2 The initial survey includes the following stages which may be performed simultaneously:

assessment of the yacht compliance with the PC Rules and other RS rules (if applicable) for the determination of the degree of the yacht compliance with the PC Rules (refer to 3.4);

verification of strength characteristics of the yacht's hull for compliance with the RS Rules, including calculation of permissible residual scantlings of hull members made of steel and aluminium alloys in accordance with the RS rules, stability calculations, gross and net tonnage calculations, freeboard calculations, inclining test, development of documentation on stability, as applicable (refer to 3.5);

performance of the initial survey (refer to 3.6).

3.3 For the classification of yachts flying the RF flag without assignment of class (refer to 1.1.3), the initial survey shall be preceded by a preliminary review of the documentation and examination of the yacht for confirmation of its technical characteristics with the purpose of yacht registration in one of the registers of ships of the Russian Federation (hereinafter referred to as "registers of ships").

Based on the results of the preliminary review of documentation and examination of the yacht, the RS surveyor shall draw up the Conclusion on the Results of Identification and Examination of the Ship (form 6.3.82rf) where only technical characteristics of the yacht without indication of compliance of items of technical supervision with the RS rules requirements are specified.

For the yachts which have previously undergone registration in one of the registers of ships and have valid documents (for example, SSVI¹ Vessel Certificate), performance of preliminary review (identification and examination) and verification of technical characteristics are not required, unless otherwise will be stated by the authorities carrying out registration of vessels.

- 3.4 Assessment of the yacht compliance with the PC Rules and other RS rules.
- **3.4.1** The assessment is carried out by the RS Branch Office on board the yacht for the determination of the degree of the yacht compliance with the RS rules taking into account the provisions of 2.2 and 2.3 of these Guidelines.
- **3.4.2** During the yacht assessment, the completeness of compliance of its hull, arrangements, equipment and outfit, machinery installation, electrical equipment with the RS rules requirements (taking into account <u>2.4</u> of these Guidelines) as regards characteristics, design and list of required items, their location and installation are determined.
- **3.4.3** To provide high quality of assessment, the plans and technical documentation in sufficient scope shall be submitted by the shipowner to the RS surveyor. Sufficiency of documentation is determined by the RS surveyor on board the yacht. Missing documentation shall be developed additionally.
- **3.4.4** The results of assessment are drawn up as a report which shall contain a list of nonconformities to be eliminated for the ship compliance with the RS rules prior to completion of the classification. For this purpose, the Report on Survey of the Ships as per form 6.3.10 or the form of the Report on Assessment of Ship's Compliance with the RS Rules given in 5.1.5.7 of Part II "Carrying Out Classification Surveys of Ships" of the TSSS Guidelines may be used.
- **3.4.5** The shipowner shall develop measures to bring the yacht into compliance with the RS rules. The measures shall contain methods and technologies for the yacht refitting.

The measures shall be reviewed and approved by the RS Branch Office performing the initial survey.

¹ State Small Vessel Inspectorate of the Ministry of the Russian Federation for Civil Defense, Emergencies and Elimination of Consequences of Natural Disasters.

3.4.6 Where the shipowner considers that the elimination of any nonconformities is impossible or impracticable, he shall make calculations, appropriate tests and take other actions allowing apply equivalents or deviations from the RS rules requirements.

The possibility of applying equivalents or deviations from the RS rules requirements, as well as calculations, results of tests and other actions allowing apply such equivalents or deviations shall be considered by RHO.

The list of equivalents is sent by RHO to MA for agreement.

- **3.4.7** Assessment of yachts constructed to the ACS QSCS class, but which have lost it (refer to 2.7.3.8) shall be carried out to the extent sufficient for confirmation that no alterations are made to the yacht during its being without the ACS QSCS class.
 - 3.5 Making calculations and documentation development.
- **3.5.1** In cases defined by the conditions of classification (refer to <u>2.7</u>), the calculations shall be made and the documentation shall be developed taking into account the following.
- 3.5.2 Verification of strength characteristics of the yacht's hull for compliance with the RS rules.
- **3.5.2.1** Verification of strength characteristics of the yacht's hull for compliance with the RS rules taking into account the provisions of $\underline{2.2}$ and $\underline{2.3}$ of these Guidelines shall include the following:

calculation of the hull member scantlings required by the RS rules;

verification of compliance of the as-built scantlings of hull members with the scantlings required by the RS rules;

calculation of permissible residual scantlings of hull members made of steel and aluminium alloys in accordance with the RS rules for all hull members regulated by the RS rules.

- **3.5.2.2** Determination of permissible scantlings of the yacht hull structures shall be carried out in accordance with Annex 2 to the CSSS Rules.
- **3.5.2.3** The calculations may be made at the shipowner's choice either by the shipowner, the Register or the competent organization.
- **3.5.2.4** When the calculations are not made by the Register, such calculations shall be submitted to RHO for review. The calculations may be reviewed by the RS Branch Office having necessary resources.
- **3.5.2.5** The calculations agreed with the Register shall be available to the RS surveyor who performs the initial survey, by the commencement of assessment of the hull structure technical condition but, in any case, no later than the classification is completed.
- **3.5.2.6** When, based on the calculation results, it will be determined that the strength characteristics of the yacht's hull do not comply with the RS rules, the shipowner shall develop measures for bringing the strength characteristics of the yacht hull into compliance with the RS rules. The measures shall contain methods and technologies of the yacht outfitting which, if necessary, shall be confirmed by calculations.

The measures shall be submitted to RHO for review. The measures may be reviewed by the RS Branch Office having necessary resources.

- 3.5.3 Plans and documentation.
- **3.5.3.1** Plans and technical documentation as required by <u>2.7.1.3</u>, <u>2.7.2.4</u> and <u>2.7.3.3</u>, shall be submitted to the RS surveyor who performs the initial survey for reviewing the applicability to the yacht subject to classification.
- **3.5.3.2** The documentation shall contain the Owner's Manual complying with the provisions of 3.5 of General Regulations of the PC Rules.
- **3.5.3.3** Missing documentation shall be additionally developed and may be submitted in the form of diagrams, sketches, descriptions, etc.
- **3.5.3.4** One copy of a set of the required plans and documents shall be submitted to the RS surveyor who performs the yacht survey, for uploading in the yacht's file.
 - 3.5.4 Documentation on stability.
- **3.5.4.1** In cases specified in <u>2.7.1.6</u> and <u>2.7.2.7</u> the documentation on stability available on board is temporarily approved by the RS surveyor for a period not more than 12 months if any deficiencies not affecting the safe operation of the yacht are found, in other cases it is approved

for a full term. In case of revealing of the above-mentioned deficiencies, the requirement on their rectification is imposed. This documentation may be available both as a separate Stability Booklet and the reference data as part of the Owner's Manual specified in 3.5.3.2.

- **3.5.4.2** The final review of documentation on stability being temporarily approved, is performed by RHO. The documentation may be reviewed and approved by the RS Branch Office having necessary resources.
- **3.5.4.3** In all cases where no documentation on stability is available on board the yacht, such documentation shall be developed in compliance with the requirements of the applicable RS rules.
- **3.5.4.4** Newly developed documentation on stability shall be based on the values of displacement and the coordinates of the centre of gravity in the lightship condition obtained from the inclining test.
- **3.5.4.5** The documentation on stability for the yachts of $L_H \le 24$ m shall take into account the downflooding height in compliance with the requirements of the PC Rules.
- **3.5.4.6** The review and approval of newly developed documentation on stability is performed by RHO. The documentation may be reviewed and approved by the RS Branch Office having necessary resources. The Inclining Test Report verified by the RS surveyor shall be attached to the documentation to be submitted for review.
- **3.5.4.7** Newly developed documentation on stability approved by the Register shall be available on board the yacht prior to completion of classification or expiry of the validity of temporarily approved documentation on stability if <u>3.5.4.1</u> is applied.

3.5.5 Tonnage calculation.

- **3.5.5.1** Calculation of gross and net tonnage shall be made in accordance with the RS rules (taking into account the provisions of <u>2.2</u>, <u>2.3</u> and <u>2.4</u> of these Guidelines), the provisions of the International Convention on Tonnage Measurement of Ships, 1969 (TONNAGE-69) or regulations of the flag State MA, as applicable.
- **3.5.5.2** The calculation execution and review is arranged by RHO. The calculation may be reviewed by the RS Branch Office having necessary resources.
- **3.5.5.3** The calculation shall be made and be available to the RS surveyor on board the yacht prior to completion of classification thereof.

3.5.6 Freeboard calculation.

- **3.5.6.1** Freeboard calculation shall be made in compliance with the RS rules (taking into account the provisions of <u>2.2</u>, <u>2.3</u> and <u>2.4</u> of these Guidelines), the provisions of the International Load Line Convention, 1966 (LL-66) as amended or regulations of the flag State MA, as applicable.
- **3.5.6.2** The calculation execution and review is arranged by RHO. The calculation may be reviewed by the RS Branch Office having necessary resources.
- **3.5.6.3** The calculation shall contain the drawings of the load line mark and details of marking.
- **3.5.6.4** The calculation shall be made and be available to the RS surveyor on board the yacht prior to completion of the yacht classification.

3.6 Initial survey.

- **3.6.1** The initial survey of yachts is performed in the scope defined by the procedures given in <u>2.7</u> taking into account the provisions of this Chapter.
- **3.6.2** Taking into account the provisions of <u>2.4</u>, the initial survey shall include survey of the life-saving appliances and fire-fighting equipment, radio-, navigational equipment, facilities for environment pollution prevention and the load line marks for compliance with the PC Rules. Where the national standards of the flag State (except for the RF MA) are available, the survey is carried out for compliance with these standards subject to the availability of the appropriate authorization from the flag State MA.

3.6.3 Initial survey of yachts classed by ACS QSCS.

3.6.3.1 The initial survey is carried out in the scope prescribed by 5.2 of Part II "Carrying Out Classification Surveys of Ships" of the TSSS Guidelines taking into account the List of Surveys Status issued by ACS QSCS.

- **3.6.3.2** Technical condition of hull structure shall be determined in accordance with <u>3.13</u>.
- **3.6.3.3** During the survey, the scheduled maintenance performed by a specialized firm in accordance with the instructions of the hull, machinery and systems manufacturers shall be taken into account.
- **3.6.3.4** Active means of the ship's steering, including steerable propellers, waterjets and outboard motors shall be serviced by a specialized firm in accordance with the manufacturer's instructions and submitted to the RS surveyor in operation for the purpose intended.
- **3.6.3.5** Taking into account <u>3.6.2</u>, radio-, navigational equipment, life-saving appliances and fire-fighting equipment and outfit, navigation lights and sound signal means as well as facilities for environment pollution prevention shall comply with the requirements of the PC Rules as applied to the assigned category with account taken of the already installed equipment.
- **3.6.3.6** Reporting documents on results of survey shall contain the requirement on the availability of the RS-approved documentation on stability on board the yacht imposed within the period not exceeding 12 months after completion of the classification if any deficiencies are found.
- **3.6.3.7** Load line marks (where prescribed) shall be marked in accordance with the drawings of the load line mark and details of marking specified in the freeboard calculation.
- **3.6.3.8** Area and conditions of navigation as well as terms of periodical surveys are assigned depending on the yacht category in accordance with 4.2 of "General Regulations" of the PC Rules and <u>3.7</u> of these Guidelines taking into account the data submitted by the losing society.
- 3.6.4 Initial survey of yachts not classed by ACS QSCS but complying with the appropriate safety standards applied by the Register (refer to 2.7.2.1).
- **3.6.4.1** The initial survey is carried out in full scope of special survey for all items of the RS technical supervision covered by the PC Rules in accordance with 5.3 of Part II "Carrying Out Classification Surveys of Ships" of the TSSS Guidelines.
- **3.6.4.2** Underwater hull of the yacht shall be surveyed in dry dock or on a slipway. Performance of in-water survey in lieu of survey of the outside of the yacht bottom (bottom survey) in dry dock using the approved procedures shall be reviewed by RHO in each particular case.
- **3.6.4.3** For the yachts of 5 years of age and over, the normal survey of shafting (if any) shall be carried out unless other term is specified by the manufacturer.
- **3.6.4.4** Active means of the ship's steering, including steerable propellers, waterjets and outboard motors shall be serviced by a specialized firm in accordance with the manufacturer's instructions and submitted to the RS surveyor in operation for the purpose intended.
 - **3.6.4.5** Technical condition of hull structures shall be determined in accordance with 3.13.
- **3.6.4.6** During the survey, the scheduled maintenance performed by a specialized firm in accordance with the instructions of the hull, machinery and systems manufacturers, shall be taken into account.
- **3.6.4.7** Taking into account <u>3.6.2</u>, radio-, navigational equipment, life-saving appliances and fire-fighting equipment and outfit, navigation lights and audible signal means as well as facilities for environment pollution prevention shall comply with the requirements of the PC Rules as applied to the assigned category with account taken of the already installed equipment.
- **3.6.4.8** The onboard documentation on stability is temporarily approved by the RS surveyor for a period not more than 12 months if any deficiencies not affecting the safe operation of the yacht are found, in other cases it is approved for a full term. In case of revealing of the above-mentioned deficiencies, the requirement on their rectification is imposed. For the final review and approval, the documentation shall be submitted by the shipowner to RHO. The documentation may be reviewed and approved by the RS Branch Office having necessary resources.
- **3.6.4.9** Reporting documents on results of survey shall contain the requirement on the availability of the RS-approved documentation on stability on board the yacht imposed within

the period not exceeding 12 months after completion of the classification if any deficiencies are found.

- **3.6.4.10** Load line marks (where prescribed) shall be marked in accordance with the drawings of the load line mark and details of marking specified in the freeboard calculation.
- **3.6.4.11** Area and conditions of navigation as well as terms of periodical surveys are assigned depending on the yacht category in accordance with 4.2 of "General Regulations" of the PC Rules and 3.7 of these Guidelines.
- 3.6.5 Initial survey of yachts not classed by ACS QSCS and not complying with the appropriate safety standards applied by the Register.
- **3.6.5.1** The initial survey is carried out in full scope of the special survey for all items of the RS technical supervision covered by the PC Rules in accordance with 5.3 of Part II "Carrying Out Classification Surveys of Ships" of the TSSS Guidelines.
 - **3.6.5.2** Underwater hull of the yacht shall be surveyed in dry dock or on a slipway.
 - 3.6.5.3 Normal survey of shafting (if any) shall be carried out.
- **3.6.5.4** Active means of the ship's steering, including steerable propellers, waterjets and outboard motors shall be serviced by a specialized firm in accordance with the manufacturer's instructions and submitted to the RS surveyor in operation for the purpose intended.
 - **3.6.5.5** Technical condition of hull structures shall be determined in accordance with 3.13.
- **3.6.5.6** During the survey, the scheduled maintenance performed by a specialized firm in accordance with the instructions of the hull, machinery and systems manufacturers, may be taken into account by the Register. Consideration of such possibility is within the competence of the RS Branch Office performing the initial survey.
- **3.6.5.7** During the initial survey, the RS-approved actions shall be performed, as stated in <u>3.4.5</u> and <u>3.5.2.5</u>.
- **3.6.5.8** Taking into account <u>3.6.2</u>, radio-, navigational equipment, life-saving appliances and fire-fighting equipment and outfit, navigation lights and audible signal means as well as facilities for environment pollution prevention shall comply with the requirements of the PC Rules as applied to the assigned category.
- **3.6.5.9** Load line marks (where prescribed) shall be marked in accordance with the drawings of the load line mark and details of marking specified in the freeboard calculation.
- **3.6.5.10** Area and conditions of navigation as well as terms of periodical surveys are assigned depending on the yacht category in accordance with 4.2 of "General Regulations" of the PC Rules and 3.7 of these Guidelines based on conditions of strength, stability and freeboard.
 - 3.7 Periodical surveys.
- **3.7.1** Depending on the assigned descriptive notation and length of the yacht, periodical surveys of the yachts are assigned taking into account 3.7.1.1 3.7.1.4.
- **3.7.1.1** Periodical surveys of the yachts with descriptive notation **Pleasure yacht** and length of $L \le 24$ m are assigned in accordance with 2.1.4 of Part I "Classification" of the PC Rules.
- **3.7.1.2** Periodical surveys of the yachts with descriptive notation **Pleasure yacht** and length of L > 24 m, as well as of all yachts with descriptive notation **Yacht (charter)** are assigned in accordance with the following:

special surveys are performed once in 5 years taking into account 2.4.1.4.5 of Part II "Survey Schedule and Scope" of the CSSS Rules (refer to 3.10 of these Guidelines);

annual surveys are performed in accordance with 2.2.1.4 of Part II "Survey Schedule and Scope" of the CSSS Rules (refer to 3.8 of these Guidelines);

intermediate surveys are performed instead of the second and third annual surveys (refer to 3.9 of these Guidelines), the surveys shall, as far as practicable, be performed simultaneously with surveys of the outside of the yacht's bottom stipulated by these Guidelines.

Bottom survey is performed in accordance with 2.5.3 of Part II "Survey Schedule and Scope" of the CSSS Rules (refer to 3.11 of these Guidelines).

3.7.1.3 Periodical surveys (including bottom survey) of the yachts with descriptive notations **Yacht for commercial service**, **Passenger yacht** and **Passenger ship** are assigned

in accordance with Section 2 of Part II "Survey Schedule and Scope" of the CSSS Rules, herewith the schedule of bottom survey for yachts with descriptive notations **Passenger yacht** and **Passenger ship** is assigned in accordance with 2.5.4.1 of Part II "Survey Schedule and Scope" of the CSSS Rules.

- **3.7.1.4** In case of additional descriptive notations in the class notation affecting the survey scope and procedure, such surveys shall be performed in addition to those specified in 3.7.1.1 3.7.1.3.
- **3.7.2** Periodical surveys of yachts flying the RF flag irrespective of their length, and classed without assignment of the RS class (refer to <u>1.1.3</u>), are assigned in accordance with 3.7.1.1.
 - 3.8 Annual survey.
- **3.8.1** Summarized scope of survey is given in 2.2 of Part II "Survey Schedule and Scope" of the CSSS Rules.
 - 3.9 Intermediate survey.
- **3.9.1** Summarized scope of survey is given in 2.3 of Part II "Survey Schedule and Scope" of the CSSS Rules.
 - 3.10 Special survey.
- **3.10.1** Summarized scope of survey is given in 2.4 of Part II "Survey Schedule and Scope" of the CSSS Rules taking into account the provisions of 3.10.2 3.10.4 of these Guidelines.
 - 3.10.2 Scope of tank survey.

Irrespective of the requirements of 2.4.2.2.3 of Part II "Survey Schedule and Scope" of the CSSS Rules, the scope of tank survey is established in compliance with <u>Table 3.10.2</u> of these Guidelines.

Table 3.10.2 Minimum requirements for internal examination at hull special surveys of fuel oil, fresh oil, fresh water and other tanks

	iresii watei and other tarks				
Nos.	Tank	Special survey No.1 age ≤ 5	Special survey No.2 5 < age ≤ 10	Special survey No.3 10 < age ≤ 15	Special survey No.4 and subsequent age > 15
1	Fuel oil bun	ker tanks:			
	.1 in engine room	None	None	One	One
	.2 outside engine room	None	One	One	Two
2	Lube oil tanks	None	None	None	One
3	Fresh water tanks	None	One	All	All

Notes: 1. All requirements of this Table apply to tanks of integral (structural) type.

- 2. If a selection of tanks of several types is accepted to be examined, then different tanks shall be examined at each special survey, on a rotation basis.
- 3. Peak tanks (all uses) are subject to internal examination at each special survey.
- 4. At special surveys starting from special survey No.3, a deep tank for fuel oil outside the engine room shall be included, if fitted.

3.10.3 Extent of testing of tanks and other spaces.

3.10.3.1 Boundaries of double bottom ballast tanks, other ballast tanks, deep, peak and other tanks adapted for the carriage of water ballast, shall be tested with a head of liquid to the top of air pipes.

Boundaries of fuel oil, lube oil, fresh water and other liquid tanks, and any independent tanks shall be tested with a head of liquid to the highest point that liquid may rise under service conditions.

3.10.3.2 The necessity of testing of ballast, fuel oil, lube oil and fresh water tanks is determined by the surveyor based on results of external examination of the tank boundaries as

well as adjacent structures and a confirmation from the master stating that the pressure testing has been carried out according to the requirements with satisfactory results, this testing shall be completed within three months prior to special survey completion.

- **3.10.3.3** The necessity of testing of tank in the engine room is determined by the RS surveyor based on results of external examination of the tank boundaries and a confirmation from the master stating that during operation of the yacht no defects and tightness damages have been found.
 - **3.10.3.4** The surveyor may extend the tank testing as deemed necessary.
 - 3.10.4 Residual thickness measurement.
- **3.10.4.1** Depending on the yacht age, thickness measurements of metal hull structures shall be carried out to the extent specified in Table 3.10.4.1.

Table 3.10.4.1

Minimum requirements for thickness measurements at special surveys				
Special survey No.1	Special survey No.2	Special survey No.3	Special survey No.4	
age ≤ 5	5 < age ≤ 10	10 < age ≤ 15	and subsequent	
			age > 15	
1. Suspect areas	1. Suspect areas	1. Suspect areas	1. Suspect areas	
throughout the yacht	throughout the yacht	throughout the yacht	throughout the yacht	
	2. One transverse section	2. Two transverse	2. Three transverse	
	of deck plating within	sections within	sections within the	
	the amidships 0,5L	the amidships 0,5L	amidships 0,5L	
		3. Internals in forepeak	3. Internals in forepeak	
		and afterpeak ballast	and afterpeak ballast	
		tanks	tanks	
			4. All open parts of main	
			deck plating full length	
			5. Representative	
			exposed superstructure	
			deck plating (poop, bridge,	
			and forecastle deck)	
			6. All wind and water	
			strakes, port and	
			starboard, full length	
			7. All keel plates, full	
			length. Also, additional	
			bottom plates in way of	
			cofferdams, machinery	
			space and aft end of tanks	
			8. Plating of sea	
			chests/ice boxes. Shell	
			plating in way of	
			overboard discharges, as	
			considered necessary by	
			the attending surveyor	

N o t e s : 1. Thickness measurement locations shall be selected to provide the best representative sampling of areas likely to be most exposed to corrosion, considering cargo and ballast history and arrangement and condition of protective coatings.

- 2. Thickness measurements of internals may be specially considered by the surveyor if the hard protective coating is in GOOD condition.
- 3. For yachts less than 100 m in length, the number of transverse sections required at special survey No.3 may be reduced to one (1), and the number of transverse sections required at special survey No.4 and at subsequent special surveys may be reduced to two (2).
- 4. For yachts more than 100 m in length, at special survey No.3, thickness measurements of exposed deck plating within the amidships 0.5L may be required.
- 5. Transverse sections shall be chosen where the largest reductions are suspected to occur or are revealed from deck plating measurements.
- 6. At least one transverse section shall include ballast tank as far as practicable.

3.10.4.2 Technical condition of metal hull structures of the commercial yachts with $L \ge 24$ m shall be determined in accordance with 5.12 of Part I "General Provisions" and Annex 2 to the CSSS Rules, and, additionally for structures made of aluminium alloy — in accordance with Section 24 of Part III "Additional Surveys of Ships Depending on Their Purpose and Hull Material" of the CSSS Rules. Technical condition of hull structures made of other materials — in

accordance with the provisions of Sections 15 and 23 of Part III "Additional Surveys of Ships Depending on Their Purpose and Hull Material" of the CSSS Rules.

- **3.10.4.3** Technical condition of hull structures of the yachts not mentioned in <u>3.10.4.2</u>, shall be determined in accordance with 3.13.
 - 3.11 Survey of the outside of the yacht bottom (bottom survey).
- **3.11.1** Summarized scope of bottom survey is assumed in compliance with the applicable requirements of 2.5 of Part II Part II "Survey Schedule and Scope" of the CSSS Rules.
 - 3.12 Survey of shafting, propellers and AMSS.
- **3.12.1** Schedule and scope of survey of shafting, propellers and AMSS shall be performed for all yachts in accordance with 2.11 of Part II "Survey Schedule and Scope" of the CSSS Rules.
 - 3.13 Assessment of technical condition of hull members.
- **3.13.1** For assessment of technical condition of hull structures, the permissible wear limits given in <u>Table 3.13.1</u> shall apply.

Table 3.13.1

Nos.	Compliance with safety standards	Material of hull members	
		Steel	Aluminium alloy
1	Yachts classed by ACS QSCS	Limits of losing ACS QSCS	Limits of losing ACS QSCS
	taking into account 2.7.1.5		or 20 % if the limits are not
			defined
2	Yachts having no class of ACS	Limits established by the	Limits established by the
	QSCS but complying with	manufacturer or the	manufacturer or the accepted
	safety standards taking into	accepted safety standard,	safety standard, or 20 % if
	account <u>2.7.2.6</u>	or 30 % if the limits are not	the limits are not defined
		defined	
3	Yachts having no class of ACS	Limits calculated based on	20 %
	QSCS and not complying with	RS rules	
	safety standards		
4	Yachts having no class of ACS	30 % or, where available,	20 % or, where available,
	QSCS and not complying with	the limits of losing society to	the limits of losing society to
	safety standards, but	the class of which the yacht	the class of which the yacht was
	constructed to the class of ACS	was constructed	constructed
	QSCS		

3.13.2 Assessment of technical condition of hull members made of aluminium alloys.

Hull structures made of aluminum alloys shall be thoroughly examined for the integrity of the structures, as well as for the absence of:

damage of paint coating and oxide coating resulting in rapid destructive corrosion; cracks in the plating and framing;

intergranular and film corrosion that are characterized by distinctive gray bloom, deep pits, bulging and delamination of metal;

loose rivets;

damage of insulating material at connections with other metals.

3.13.3 Assessment of technical condition of hull members made of glass-reinforced plastic and other composite materials.

Hull structures made of glass-reinforced plastic and other composite materials shall be thoroughly examined for the integrity of the structures, as well as for the absence of:

plating lamellar tear and leaks in joints;

matting-in connections detachment from the plating and framing members;

cracks on the plating and framing;

changing of actual geometric hull parameters (length, breadth, freeboard depth, keel line) as compared to those given in the specification;

other defects affecting the outer contour watertightness and hull structure strength.

3.13.4 Assessment of technical condition of hull members made of wood.

Hull structures from wood shall be thoroughly examined for the integrity of the structures, as well as for the absence of:

worm channels in outer plating;

mechanical wear and rot in planks and longitudinals to a depth where the holding power of metal fastenings is reduced or seams and butts of outer plating or deck plating are weakened due to damage to caulking and leakage occurrence;

local rot in the transverses and stems due to timber damage to a depth greater than 1/3 of the plank timber thickness;

rot in floor timbers and futtocks to a depth greater than 1/4 of the plank timber thickness at selected areas with the total number of rotten girders above 20 % of the girders in the area between strength structural bulkheads;

rot in case of continuous damage to a depth greater than 1/5 of the thickness of futtocks or floor timers in five of more successive girders;

girders with significant mechanical damage such as breaks, burrs, cracks and shearing that may affect the strength or tightness;

wear of metal fixing heads for more than 1/3 of their height and reduction of bolt and nail diameter for more than 1/10 of the initial value;

delamination of bonded parts of plating and framing.

4 RS DOCUMENTS

- **4.1** Considering of issues of application of the RS forms of documents to the yachts, as well as their filling-in is within the RHO competence.
- **4.2** The results of initial and special survey of the yacht with descriptive notation **Pleasure yacht** or **Yacht(charter)** in the class notation shall be recorded in the Report on Initial/Special Survey of Pleasure Craft (form 6.3.77). The results of the initial and special survey of the yachts with descriptive notations **Yacht for commercial service**, **Passenger yacht** or **Passenger ship** in the class notation shall be drawn up in accordance with the applicable provisions of Section 6 "Documents Drawn up by the Register" of Part I "General Provisions" of the TSSS Guidelines.
 - 4.3 Drawn up documents.
- **4.3.1** Upon satisfactory results of the initial survey, the following documents shall be issued to the yacht less than 24 m in length, with descriptive notation **Pleasure yacht** in the class notation regardless of nationality, taking into account <u>4.5</u> of these Guidelines:

Classification Certificate (form 3.1.9);

Equipment Certificate (form 4.1.1rf);

Certificate for the Prevention of Pollution from Ships (form 2.4.18rf);

Certificates as per forms 4.1.1rf and 2.4.18rf confirm the compliance of the yacht with the requirements of the PC Rules.

4.3.2 Upon satisfactory results of the initial survey, the following documents shall be issued to the yacht of 24 m in length and above, with descriptive notation **Pleasure yacht** in the class notation and yachts with descriptive notation **Yacht (charter)** in the class notation regardless of nationality, taking into account <u>4.5</u> of these Guidelines:

Classification Certificate (form 3.1.9);

Equipment Certificate (form 4.1.1rf);

Certificate for the Prevention of Pollution from Ships (form 2.4.18rf);

Load Line Certificate (form 1.3.3) (only for yachts with descriptive notation **Yacht (charter)** in the class notation).

Certificates as per forms 4.1.1rf, 2.4.18rf and 1.3.3 confirm the compliance of the yacht with the requirements of the PC Rules.

4.3.3 Upon satisfactory results of the initial survey, the following documents shall be issued to the yachts with descriptive notation **Yacht for commercial service**, **Passenger yacht** or **Passenger ship** in the class notation:

Classification Certificate (form 3.1.2):

other applicable documents prescribed by Section 6 of Part I "General Provisions" of the TSSS Guidelines.

- **4.4** Based on the Tonnage calculation, the Tonnage Certificate as per form 1.2.12 shall be issued to the yacht.
- **4.5** Where issuance of other certificates confirming the compliance with the national requirements is prescribed by the flag State MA (except for the RF MA), such certificates shall be issued instead of those certificates prescribed by <u>4.3</u> and <u>4.4</u> (except for the Classification Certificate).
- **4.6** Where the yacht engagement in international voyages is planned by the shipowner, the following international certificates required by the applicable international conventions shall be issued to the yacht upon completion of the appropriate surveys instead of the certificates specified in <u>4.3</u> and <u>4.4</u> taking into account the following.
- **4.6.1** The International Convention for the Safety of Life at Sea, 1974, as amended by the Protocol 1978 relating thereto (SOLAS 74/78) shall apply to the yachts intended for commercial use with issuance of the appropriate certificates.
- **4.6.2** International Convention for the Prevention of Pollution from Ships, 1973, as modified by the Protocol 1978 relating thereto (MARPOL 73/78):

Annex I — shall apply to all yachts, the appropriate certificate shall be issued to the yachts of 400 gross tonnage and above;

Annex IV — shall apply to yachts of 400 gross tonnage and above as well as of gross tonnage below 400 when more than 15 persons are carried on board, the appropriate certificate shall be issued:

Annex V — shall apply to all yachts, the appropriate certificate shall be issued if prescribed by the Agreement between MA and RS;

Annex VI — shall apply to all yachts, the appropriate certificate shall be issued to the yachts of 400 gross tonnage and above.

- **4.6.3** LL-66, as amended, shall apply to yachts engaged in commercial transportation, of 24 m in length and above with issuance of the appropriate certificate.
- **4.6.4** TONNAGE-69, as amended, shall apply to yachts of 24 m in length and above with issuance of the appropriate certificate. Where the International Tonnage Certificate is issued to the yacht which earlier had a similar certificate according to TONNAGE-69 issued by ACS QSCS or the flag State MA, without additional tonnage calculation, it is permitted not to indicate the space volumes in the new certificate if they were not specified in the certificate issued by ACS QSCS or the flag State MA.
- **4.7** In case of classification of the ACS QSCS-classed yachts of gross tonnage above 100, the Summary Report on Ship's Transfer/Adding of Double/Dual Class shall be issued as per form 6.3.50.
- **4.8** The results of special survey of the yacht shall be recorded in the Report on Initial/Special Survey of Pleasure Craft as per form 6.3.77. Upon satisfactory results of special survey, the certificates specified in <u>4.3</u> shall be renewed for the yacht.
- **4.9** The results of annual or intermediate survey of the yacht with descriptive notation **Pleasure yacht** or **Yacht (charter)** in the class notation shall be recorded in the Report on Annual/Intermediate Survey of Pleasure Craft (form 6.3.77.1), for yachts with other descriptive notations in the class notation, the results of periodical surveys shall be drawn up in accordance with Section 6 of Part I "General Provisions" of the TSSS Guidelines. Upon satisfactory results of survey, the certificates specified in <u>4.3</u> of these Guidelines shall be endorsed.
- **4.10** During classification of yachts flying the RF flag without assignment of the RS class (refer to $\underline{1.1.3}$), in amendment of the provisions of $\underline{4.2 4.9}$, the documents shall be drawn up in the following bellow way.
- **4.10.1** Initially, for registration of the yacht in one of registers of ships, the RS surveyor shall fill in the Conclusion as per form 6.3.82rf where only the technical characteristics of the yacht are specified (refer to <u>3.3</u>). The Conclusion witnessed by the RS surveyor shall be given to the shipowner for submitting to the authorities carrying out registration of vessels. For the yachts which has previously undergone registration in one of the registers of ships and have valid documents (for example, SSVI Vessel Certificate), performance of identification and examination is not required, unless otherwise will be stated by the authorities carrying out registration of vessels.
- **4.10.2** Upon registration of the yacht in one of the registers of ships, the yacht classification shall be carried out with performance of initial survey, the results of which shall be indicated in the Report as per form 6.3.77. In the Report, the RS surveyor shall specify the compliance of technical condition of the items of technical supervision with the RS rules and indicate the established restrictions on the area and conditions of navigation.
- **4.10.3** Tonnage calculation and issuance of the Tonnage Certificate shall be carried out at the shipowner's request if required by the authorities carrying out registration of vessels. Form of the Tonnage Certificate to be issued shall be agreed with RHO in each particular case.
 - **4.10.4** At special survey, the Report as per form 6.3.77 shall be issued.
 - **4.10.5** At intermediate survey, the Report as per form 6.3.77.1 shall be issued.

Российский морской регистр судоходства

Руководство по классификации и освидетельствованию яхт

Russian Maritime Register of Shipping

Guidelines on the Classification and Survey of Yachts

FAI "Russian Maritime Register of Shipping" 8, Dvortsovaya Naberezhnaya, 191186, St. Petersburg, Russian Federation www.rs-class.org/en/